

-25 C Biomedical Freezer - 25F3



Model	DW-25L92
Exterior Dimensions (WxDxH)	25.8" x 27" x 65.55"
Interior Dimensions (WxDxH)	18.9" x 18.3" x 56.30"
Temp Range	-10°C ~ -25°C
Interior Capacity	3.2 cu.ft./92 L
Drawers	3
Sound Level	27 dB
Defrost Mode	Manual

Overview

*Underbench -25°C biomedical freezer, 92L capacity, manual defrost and 3 internal drawers. Reliable, energy-efficient and environmentally friendly HC refrigeration. Microprocessor controller, LED display with battery backup, alarm functions and lock.

Hydrocarbon Energy-saving

*25F3 adopts an efficient hydrocarbon (HC) compressor and optimized refrigeration system, to give a power consumption of just 0.65KW·h/24h.

Environmentally Friendly

*The HC system is a completely green refrigeration solution.

Low Noise

*Optimized hydrocarbon system and structural noise reduction design, the 25F3 noise level is 27 dB. Super quiet and low noise.

Security Lock

* Mechanical lock plus lock catch, the mechanical door lock can be opened with one key, and the door lock can be padlocked. Secure and safe, suitable for multiple users.

Microprocessor

- * Microprocessor electronic temperature controller, LCD digital temperature display, display precision is 0.1° C, temperature set point $-10\sim-25^{\circ}$ C.
- *Multiple alarms including high and low temperature, sensor error, power failure, door ajar, high ambient and remote alarm.
- *Alarm mode: sound and light alarm.
- *Capable of connecting to remote alarm.

Porthole

*There is a standard access port on the left side of the unit, which is convenient for users to test independently



Geneva Scientific LLC P.O. Box 408 Fontana, WI 53125 1-877-436-3827 Fax: 262-607-6497

Sales@Geneva-Scientific.com

Specifications are subject to change without notice.

rev. 01/22